



HHK 5AL

Hydraulic Impact Hammer

JUNTTAN HHK 5AL		
Max. energy	kNm (ft-lbs)	39 (28 817)
Drop height	mm (inch)	50 - 800 (2 - 31.5)
Blows per minute		40 - 100
Ram weight	kg (lb)	5 000 (11 020)
Total weight including A-type drive cap	kg (lb)	7 600 (16 760)
Oil flow	l/min (gpm)	360 (95.8)
Operating pressure	bar (PSI)	175 (2 538)
Hoses - pressure line	mm (inch)	38 (1 ½)
- return line		38 (1 ½)
Drive cap types		A for metal tubes B for concrete piles
Drive cap max. inner diameter	mm (inch)	A: Ø 750 (29.5) B: □ 450x450 (17.7x17.7)
Larger drive cap diameters available on special request		
Suitable power packs		5 CCU - 30 CCU
Optional equipment		
<ul style="list-style-type: none"> • guide claws • energy measurement device 	<ul style="list-style-type: none"> • additional drive caps • pile sleeves • lifting cat 	<ul style="list-style-type: none"> • power packs • additional noise insulation package

Junttan Oy reserves the right to amend the specification without prior notice. Error and misprints reserved. 3 March 2005 - version M1HHK5AL001.