



## HHK 3A Hydraulic Impact Hammer

JUNTTAN HHK 3A		
Max. energy	kNm (ft-lbs)	35 (25 900)
Drop height	mm (inch)	50 - 1200 (2 - 47.2)
Blows per minute		40 - 100
Ram weight	kg (lb)	3 000 (6 610)
Total weight including A-type drive cap	kg (lb)	6 200 (13 670)
Oil flow	l/min (gpm)	310 (81.9)
Operating pressure	bar (PSI)	110 (1 595)
Hoses - pressure line	mm (inch)	38 (1 ½)
- return line		38 (1 ½)
Drive cap types		A for metal tubes B for concrete piles
Drive cap max. inner diameter	mm (inch)	A: Ø 600 (23.6) B: □ 370x370 (14.6x14.6)
Larger drive cap diameters available on special request		
Suitable power packs		5 CCU - 30 CCU
Optional equipment		
<ul style="list-style-type: none"> <li>guide claws</li> <li>energy measurement device</li> </ul>	<ul style="list-style-type: none"> <li>additional drive caps</li> <li>pile sleeves</li> <li>lifting cat</li> </ul>	<ul style="list-style-type: none"> <li>power packs</li> <li>additional noise insulation package</li> </ul>

Junttan Oy reserves the right to amend the specification without prior notice. Error and misprints reserved. 3 March 2005 - version M1HHK3A001.