



HHK 4A

Hydraulic Impact Hammer

JUNTTAN HHK 4A		
Max. energy	kNm (ft-lbs)	47 (34 780)
Drop height	mm (inch)	50 - 1200 (2 - 47.2)
Blows per minute		40 - 100
Ram weight	kg (lb)	4 000 (8 820)
Total weight including A-type drive cap	kg (lb)	7 100 (15 650)
Oil flow	l/min (gpm)	310 (81.9)
Operating pressure	bar (PSI)	145 (2 100)
Hoses - pressure line	mm (inch)	38 (1 ½)
- return line		38 (1 ½)
Drive cap types		A for metal tubes B for concrete piles
Drive cap max. inner diameter	mm (inch)	A: Ø 600 (23.6) B: □ 420x420 (16.5x16.5)
Larger drive cap diameters available on special request		
Suitable power packs		5 CCU - 30 CCU
Optional equipment		
<ul style="list-style-type: none"> guide claws energy measurement device 	<ul style="list-style-type: none"> additional drive caps pile sleeves lifting cat 	<ul style="list-style-type: none"> power packs additional noise insulation package

Junttan Oy reserves the right to amend the specification without prior notice. Error and misprints reserved. 3 March 2005 - version M1HHK4A001.