



## HHU 10S

Hydraulic Impact Hammer



JUNTAN HHU 10S		
Max. energy	kNm (ft-lbs)	147 (108 618)
Drop height	m (ft)	0.05 – 1.5 (0.16 - 4.9)
Blows per minute		30 -100
Ram weight	kg (US ton)	10 000 (11)
Total weight incl. A-type drive cap	kg (US ton)	14 800 (16.3)
Oil flow	l/min (gpm)	340 (90)
Operating pressure	bar (PSI)	269 (3900)
Hoses - pressure line	mm (inch)	38 (1 1/2)
- return line		38 (1 1/2)
Drive cap types		A for metal tubes B for concrete piles
Drive cap max. inner diameter	mm (inch)	A: O B: □
Larger drive cap diameters available on special request		
Suitable power packs		15 CCU- 30CCU
Optional equipment		
<ul style="list-style-type: none"> <li>guide claws</li> <li>energy measurement device</li> </ul>	<ul style="list-style-type: none"> <li>additional drive caps</li> <li>pile sleeves</li> <li>lifting cat</li> </ul>	<ul style="list-style-type: none"> <li>power packs</li> <li>additional noise insulation package</li> </ul>

Junttan Oy reserves the right to amend the specification without prior notice. Error and misprints reserved. 3 March 2005 - version M1HHU10S001.